



SAE 15W-50 Technical Data Sheet

Description: TRE SAE 15W-50 Break-In engine oil is formulated for breaking in engines with tappet camshafts, roller elements, or where anti-wear performance is needed. Our high Zinc formula ensures fast and effective ring sealing with immediate and long-lasting protection.

Applications: For use in all 4-stroke engines. Designed for high performance applications incl: off-road, circle track, late model, drag, GrandAm, OEM rebuilds, crate motors, and more.

Physical Properties:

Appearance	Amber
API Gravity @ 40°F	160.4
Viscosity @ 100°C	20.6 cSt
Viscosity Index	150
Flash Point	210°C
Pour Point	-36°C
Density @ 15°C (g/ml)	.870

Method of Use: Treat current oil system according to manufacturer's specifications and owner's manual. *Do not overfill.

Storage and Handling: Keep container closed until use. Keep out of direct sunlight and heat. Discard waste appropriately.

Notes: The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any

production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof.

In light of the foregoing, TRE specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of TRE products. TRE specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any TRE patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark Usage: Except as otherwise noted, all trademarks in this document are trademarks of TRE in the USA and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office. Any and all TRE marks may not be used without prior consent.